

仕様

1)標準品(Standard type)

型式 Model	管理番号 Product No.	定格電圧 Rating Voltage [V]	使用電圧範囲 Operating Voltage [V]	周波数 Frequency [Hz]		起動電圧 Starting Voltage [V]
				50	60	
9833LT-20W-B3A-	FS0	200	180~220	50	130	
				60		
9833LT-24W-B3A-	FS0	240	180~260	50	130	
				60		
9833LT-20W-B3A-	RS0	200	180~220	50	130	
				60		
9833LT-24W-B3A-	RS0	240	180~260	50	130	
				60		

型式 Model	管理番号 Product No.	定格電流 Current [A]	定格入力 Power [W]	定格回転 数 Speed [min-1]	最大風量 Max.Air Flow [m3/min]		最大静圧 Max.Static Pressure [Pa]
					20.3	21.9	
9833LT-20W-B3A-	FS0	0.35	121	2600	20.3	255	
		0.47	179	2950	21.9	216	
9833LT-24W-B3A-	FS0	0.40	140	2650	20.4	305	
		0.45	190	3050	23.5	300	
9833LT-20W-B3A-	RS0	0.32	103	2650	17.7	202	
		0.44	138	2950	19.8	183	
9833LT-24W-B3A-	RS0	0.39	122	2700	18.3	235	
		0.41	164	3100	20.7	242	

型式 Model	管理番号 Product No.	ファン外径 Fan Diameter [mm]	ファン高さ(厚み) Fan Hight [mm]	質量 Mass [g]
9833LT-24W-B3A-	FS0	250	95.0	2900
9833LT-20W-B3A-	RS0	250	95.0	2900
9833LT-24W-B3A-	RS0	250	95.0	2900

2)高電圧対応品(High Voltage Supported type)

型式 Model	管理番号 Product No.	定格電圧 Rating Voltage [V]	使用電圧範囲 Operating Voltage [V]	周波数 Frequency [Hz]		起動電圧 Starting Voltage [V]
				50	60	
9833LT-38W-B3A-	FS0	380	340~420	50	250	
				60		
9833LT-38W-B3A-	RS0	380	340~420	50	250	
				60		

型式 Model	管理番号 Product No.	定格電流 Current [A]	定格入力 Power [W]	定格回転数 Speed [min-1]	最大風量 Max.Air Flow [m3/min]		最大静圧 Max.Static Pressure [Pa]
					19.0	21.4	
9833LT-38W-B3A-	FS0	0.17	107	2650	19.0	250	
		0.23	149	2950	21.4	210	
9833LT-38W-B3A-	RS0	0.18	112	2600	18.8	193	
		0.24	155	2900	20.7	166	

型式 Model	管理番号 Product No.	ファン外径 Fan Diameter [mm]	ファン高さ(厚み) Fan Hight [mm]	質量 Mass [g]
9833LT-38W-B3A-	RS0	250	95.0	1800