



## ■ Features

- Wide input range 100~305V AC (Class I)
- Full power output at 70~100% Constant power mode operation
- Metal case with IP67, suitable for outdoor application
- Surge protection with 6KV/4KV (10KV/6KV optional)
- 3 in 1 dimming function (Dim to off and Isolation design)
- India (EESL) version with Input Over Voltage Protection can survive input voltage stress of 440Vac for 48 hours
- Protection functions: OVP/SCP/OCP/OTP
- Life time >50,000 hrs. and 5 years warranty


## ■ Applications

- Skyscraper lighting
- Street lighting
- Floodlight Lighting
- Stage lighting
- Fishing lighting
- Horticulture lighting
- Bay lighting
- DMX power supply
- Type HL for use in class I, Division 2

## ■ Description

XLG-200 series is a 200W LED AC/DC driver featuring the constant power mode. XLG-200 operates from 100~305VAC and offers models with different rated current ranging between 700mA and 16A. Thanks to the high efficiency up to 94%, with the fanless design, the entire series is able to operate for -40°C ~+90°C case temperature under free air convection. The design of metal housing and IP67 ingress protection level allows this series to fit both indoor and outdoor applications. Moreover the innovative environment-adaptive capability allows this series to reliably light on the LEDs for all kinds of application environments in almost any spots that may install LED luminaires in the world. XLG-200 series comply with the latest version of IEC61347/GB7000.1-2015 and UL8750 international safety regulations. The output and dimming circuit are also completely in accordance with the new regulations with isolation to ensure the safety of both user and luminaire system during installation.

## ■ Model Encoding




Type	Function	Note
Blank	I <sub>o</sub> and V <sub>o</sub> fixed.(For harsh environment)	By request
A	I <sub>o</sub> adjustable via built-in potentiometer	In Stock
AB	I <sub>o</sub> adjustable via built-in potentiometer + 3 in 1 dimming function (0~10Vdc, 10V PWM signal and resistance)	In Stock


Note: 12V and 24V models without AB type

## SPECIFICATION


MODEL	XLG-200□-L-□	XLG-200□-H-□
OUTPUT	RATED CURRENT 700mA	3500mA
	RATED POWER 200W	200W
	CONSTANT CURRENT REGION Note.1 142~285V	27~56V
	FULL POWER CURRENT RANGE 700~1050mA	3500~5550mA
	OPEN CIRCUIT VOLTAGE (max.) 300V	60V
	CURRENT ADJ. RANGE Adjustable for A/A/B-Type only (via the built-in potentiometer)	
	350~1050mA	1750~5550mA
	CURRENT RIPPLE 3.0%(@ Load ≥ 50% rated voltage)	
INPUT	CURRENT TOLERANCE ± 5%	
	SET UP TIME Note.4 500ms/230VAC, 1200ms/115VAC	
	VOLTAGE RANGE Note.3 100~305VAC 142VDC~431VDC (Please refer to "STATIC CHARACTERISTIC" and "DRIVING METHODS OF LED MODULE" section)	
	FREQUENCY RANGE 47~63Hz	
	POWER FACTOR (Typ.) PF ≥ 0.97 / 115VAC, PF ≥ 0.95 / 230VAC, PF ≥ 0.92 / 277VAC at full load (Please refer to "Power Factor Characteristic" section)	
	TOTAL HARMONIC DISTORTION THD < 10% (@ load ≥ 50% at 115VAC/230VAC, @ load ≥ 75% at 277VAC) Please refer to "TOTAL HARMONIC DISTORTION (THD)" section	
	EFFICIENCY (Typ.) 94%	93%
	AC CURRENT (Typ.) 2.2A / 115VAC 1.1A / 230VAC 0.9A / 277VAC	
PROTECTION	INRUSH CURRENT(Typ.) COLD START 65A (with = 550μs measured at 50% Ipeak) at 230VAC, Per NEMA 410	
	MAX. NO. of PSUs on 16A CIRCUIT BREAKER 3 unit(circuit breaker of type B) / 6 units(circuit breaker of type C) at 230VAC	
	LEAKAGE CURRENT <0.75mA / 277VAC	
	STANDBY POWER CONSUMPTION Standby power consumption <0.5W for AB-Type(Dimming OFF)(for standard version)	
	SHORT CIRCUIT Hiccup mode or Constant current limiting, recovers automatically after fault condition is removed	
	OVER VOLTAGE 301~360V 61~85V	
	INPUT OVER VOLTAGE Note.5 320~390VAC Shut down output voltage when the input voltage exceeds protection voltage, recovers automatically after fault condition is removed Can survive input voltage stress of 440Vac for 48 hours (@ Tc 75°C, max)	
	OVER TEMPERATURE Shut down output voltage, re-power on to recover	
ENVIRONMENT	WORKING TEMP. Tcase = -40~+90°C (Please refer to "OUTPUT LOAD vs TEMPERATURE" section)	
	MAX. CASE TEMP. Tcase = +90°C	
	WORKING HUMIDITY 20~95% RH non-condensing	
	STORAGE TEMP., HUMIDITY -40~+80°C, 10~95% RH non-condensing	
	TEMP. COEFFICIENT ±0.03%/°C (0~60°C)	
	VIBRATION 10~500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes	
SAFETY & EMC	SAFETY STANDARDS Note.5 UL8750(type HL), CSA C22.2 No. 250.13-12, ENEC EN61347-1, EN61347-2-13 independent, EN62384/GB19510.1, GB19510.14/EAC TP TC 004, JIS1347-1(H29), JIS1347-2-13(H29), KC61347-1/KC61347-2-13, IS15885(Part2/Sec13); NOM-058-SCFI-2017(except for Blank type), IP67 approved	
	WITHSTAND VOLTAGE I/P-O/P: 3.75kVAC I/P-FG: 2kVAC O/P-FG: 1.5kVAC	
	ISOLATION RESISTANCE I/P-O/P, I/P-FG, O/P-FG: 100M Ohms / 500VDC / 25°C / 70% RH	
	EMC EMISSION Compliance to EN55015, EN61000-3-2 Class C (@ load ≥ 50%), EN61000-3-3	
	EMC IMMUNITY Compliance to EN61000-4-2,3,4,5,6,8,11, EN61547, light industry level(surge immunity Line-Earth 6KV, Line-Line 4KV)(10K/6KV option)	
	EMC EMISSION	
	Parameter Standard Test Level/Note	
	Conducted EN55015(CISPR15), GB/T17743 -----	
EMC IMMUNITY	Radiated EN55015(CISPR15), GB/T17743 -----	
	Harmonic Current EN61000-3-2, GB/T17625.1 Class C @load≥50%	
	Voltage Flicker EN61000-3-3 -----	
	EN61547	
	Parameter Standard Test Level/Note	
	ESD EN61000-4-2 Level 3, 6KV air ; Level 2, 4KV contact	
	Radiated EN61000-4-3 Level 3	
	EFT/Burst EN61000-4-4 Level 3	
OTHERS	Surge EN61000-4-5 4KV/Line-Line 6KV/Line-Earth/6K/10K option	
	Conducted EN61000-4-6 Level 3	
	Magnetic Field EN61000-4-8 Level 4	
	Voltage Dips and Interruptions EN61000-4-11 >95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods	
NOTE	MTBF 749.06Khrs min. Telcordia SR-332(Bellcore), 200.67Khrs min. MIL-HDBK-217F (25°C)	
	DIMENSION 199*63*35.5mm (L*W*H)	
	PACKING 0.85Kg; 16pcs/14.2Kg/0.72CUFT	
1. All parameters NOT specially mentioned are measured at 230VAC input, rated current and 25°C of ambient temperature. 2. Please refer to "DRIVING METHODS OF LED MODULE". 3. De-rating may be needed under low input voltages. Please refer to "STATIC CHARACTERISTIC" sections for details. 4. Length of set up time is measured at first cold start. Turning ON/OFF the driver may lead to increase of the set up time. 5. Input over voltage only for XLG-200 L series and I series without UL/CSA certificate. 6. The driver is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again. 7. This series meets the typical life expectancy of >30,000 hours of operation when Tcase, particularly (Tc point) or TMP, per DLC, is about 75°C or less. 8. Please refer to the warranty statement on MEAN WELL's website at <a href="http://www.meanwell.com">http://www.meanwell.com</a> 9. The ambient temperature derating of 3.5°C/1000m with fanless models and of 5°C/1000m with fan models for operating altitude higher than 2000m(6500ft). 10. To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED driver can only be used behind a switch without permanently connected to the mains. 11. Products sourced from the Americas regions may not have the CCC/PSE/BIS/KC logo. Please contact your MEAN WELL sales for more information. 12. For any application note and IP water proof function installation caution, please refer our user manual before using. <a href="https://www.meanwell.com/Upload/PDF/LED_EN.pdf">https://www.meanwell.com/Upload/PDF/LED_EN.pdf</a> 13. Ripple & noise are measured at 20MHz of bandwidth by using a 12' twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 14. To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED driver can only be used behind a switch without permanently connected to the mains. 15. If you need the NOM (Mexico) certificate, Please contact MEAN WELL sales representative for details.		

**■ BLOCK DIAGRAM**

**■ DRIVING METHODS OF LED MODULE**
**※ I-V Operating Area**

◎ XLG-200-L




◎ XLG-200-H


■ Recommend Performance Region


■ Recommend Performance Region

◎ XLG-200-12,24







- This series is able to work in either Constant Current mode (a direct drive way) or Constant Voltage mode (usually through additional DC/DC driver) to drive the LEDs.



Typical output current normalized by rated current (%)

**DIMMING OPERATION**

**① 3 in 1 dimming function (for AB-Type)**



- Output constant current level can be adjusted by applying one of the three methodologies between DIM+ and DIM-:  
0 ~ 10VDC, or 10V PWM signal or resistance.
- Direct connecting to LEDs is suggested. It is not suitable to be used with additional drivers.
- Dimming source current from power supply: 100  $\mu$ A (typ.)

**② Applying additive 0 ~ 10VDC**

**③ Applying additive 10V PWM signal (frequency range 100Hz ~ 3KHz):**

**④ Applying additive resistance:**


Note : 1. Min. dimming level is about 8% and the output current is not defined when 0% < Iout < 8%.


2. The output current could drop down to 0% when dimming input is about 0k $\Omega$  or 0Vdc, or 10V PWM signal with 0% duty cycle.

### ■ OUTPUT LOAD vs TEMPERATURE




If XLG-200 operates in Constant Power mode with the rated current the maximum workable  $T_a$  is 50  $^{\circ}$ C (Typ. 230VAC) or 40  $^{\circ}$ C (typ. 110VAC)  
Below 110VAC@30  $^{\circ}$ C may retry to 2nd setup

### ■ STATIC CHARACTERISTIC




### ■ POWER FACTOR (PF) CHARACTERISTIC



### ■ TOTAL HARMONIC DISTORTION (THD)


• XLG-200-L Model,  $T_{case}$  at 75  $^{\circ}$ C



### ■ EFFICIENCY vs LOAD

XLG-200 series possess superior working efficiency that up to 94% can be reached in field applications.


• XLG-200-L Model,  $T_{case}$  at 75  $^{\circ}$ C



### ■ MECHANICAL SPECIFICATION

Case No.:244A Unit:mm

#### ※ Blank-Type



#### ※ A-Type

